



Hopelight Electrical Co.,Ltd

Add:No 10,Fengtang Avenue,Fuhai Street,Baoan District,Shenzhen Guangdong China 518103

Polyimide tape TDS

PRODUCT NAME (产品名称)	Polyimide tape		
PRODUCT No.(产品型号)	PI2535		
ITEM (项目)	UNIT (单位)	SPEC (基准值)	TEST METHOD (实验方法)
Total Thickness(总厚度)	mm	0.06±0.002	GB7125-1998
Film Thickness(原料厚度)	mm	0.025	GB7125-1997
Glue(胶水)		Silicone	
Color(颜色)		Amber	
Length(长度)	m	33±0.5	
Adhesion (粘着力)	N/25mm	5	GB/T2792-1997
Tensile Strength (抗拉力)	N/25mm	140	GB7753-1986
Elongation (伸张率)	%	40	GB7753-1986
Voltage Resistance(耐电压)	KV	6.5	
Heat Resistance(耐热性)	℃	260℃ /30	temperate box CE-021
USAGES (用途) shielding protection during high temperature spraying of chassis, cabinets, etc., and the product is protected by high temperature in tin furnace.用于机箱、机柜等高温喷涂时的遮蔽保护，产品过锡炉高温保护。			
FEATURES (特性) Good Performance in Adhesive Force,High Temperature Resistant,Soft and Compact,Strong Holding Force,No Residual Left. (粘性好，耐高温，柔软服贴，保持力强，不残胶) 1.Substrate Material(材质): Polyimide Film (聚酰亚胺膜)+silicone(硅胶)			